

THE WILKINSBURG-PENN JOINT WATER AUTHORITY

HYDRANT METER and HYDRANT USAGE APPLICATION

Start Date _____ Authority Representative _____

Name and Address: _____

Phone Number: _____ Deposit Received \$ _____

Hydrant Number and Location: _____

The above Hydrant will be used for: _____

Hydrant and Meter Usage Fees:

- \$250.00 Deposit required at time of application
- \$20.00 Per day permit fee
- \$ _____ Per 100 cubic feet of water consumption

Terms and Conditions of Use:

- The applicant assumes full responsibility for all damage to person, equipment and property, including environmental damage which may occur from use of this hydrant and agrees to pay the costs thereof.
- If the meter and its appendages are lost, stolen or damaged then actual cost of the meter and or appendages will be charged. See back of application for replacement charges.
- The hydrant must be opened and closed slowly, using an approved hydrant wrench. The hydrant should be fully opened when in use. Regulate flows with the meter valves not the hydrant. When a hydrant is not in use, the hydrant should be shut off. The meter, hoses and all appendages should be removed from the hydrant and hydrant caps replaced.
- Resale of water from the hydrant is prohibited.
- This application is for the above hydrant or hydrants only and is non-transferable.
- WPJWA reserves the right to terminate this service for non-compliance of this policy, without notice and refund.
- The Authority reserves the right to recover any unforeseen costs that may occur with the hydrant and hydrant meter.

Although the service may be rendered during a weekend, application can only be made in person at the Authority Office during normal business hours Monday through Friday, 8:00am to 4:30pm.

I have read both sides of this application and agree to the fees, terms and conditions

Signature _____ Print _____

THE WILKINSBURG-PENN JOINT WATER AUTHORITY

Replacement Charges			
DESCRIPTION	AMOUNT	PRICE EACH	TOTALS
2" TURBINE METER	1	\$437.50	\$437.50
15' FLUSHING HOSE	1	\$130.00	\$130.00
2" VALVES	1	\$29.95	\$29.95
2" X 3" NIPPLES	2	\$14.25	\$28.50
2" BACKFLOW PREVENTER LESS VALVES	1	\$156.95	\$156.95
2-1/2" MALE NAT'L HOSE THREAD X 2" MALE NPT ADAPTER	1	\$87.95	\$87.95
2-1/2" MALE NAT'L HOSE THREAD X 2" FEMALE NPT ADAPTER	1	\$72.00	\$72.00
2-1/2" FEMALE PGH 6 THREAD X 2-1/2" MALE NAT'L HOSE THREAD ADAPTER	1	\$86.00	\$86.00
		TOTAL	\$1028.85

PROPER HYDRANT OPERATION

- Remove the 2-1/2" nozzle cap
- Connect the meter assembly hose to the hydrant nozzle.
- Open the hydrant slowly, using an approved hydrant wrench. The hydrant should be fully opened when in use.
- Regulate flows with the meter valves not the hydrant. Open and close the meter valves slowly.
- Close the hydrant slowly, especially the last 3 to 4 turns to prevent "Water Hammer" that may damage water lines.
- Remove the meter assembly from the hydrant.
- Replace the hydrant cap.
- Report any problems with the hydrant to Customer Service at 412-243-6200

REMEMBER!

When the hydrant is not in use, the hydrant should be shut off, the meter, hoses and all appendages should be removed from hydrant and hydrant caps replaced.